



Pol.Ind. L'Alteró, Av. Saler 14, 46460 Silla (Valencia), SPAIN
Tel: +34 961 216 301 | Fax: +34 961 200 242 | equipson@equipson.es

Products ▶ Audio ▶ Audio tools ▶ **AUDIOROUTE 208**



AUDIOROUTE 208

AUDIOROUTE 208 is a signal distributor featuring 2 inputs and 8 outputs. The later have an independent gain controller.

It includes DIP switch blocks to select input and output channels, and so mix inputs in a unique channel (or even mute any of the outputs). This makes this device different from the other splitters.

Source selection is done using DIP switch blocks, so there is no need to move cables to change or mix channels.

Features

- 2 inputs / 8 outputs audio signal distributor.
- 3 operating mode: Separated channels, Full attenuation and Channels mixing.
- All operating modes configurable by DIP switch.
- Vumeter for each channel level.
- Balanced input/output connectors.
- Balanced output via transformer with feed-forward control to improve low frequency distortion.
- Link output for connections with other units.

Technical data AUDIOROUTE 208

- Input impedance: Balanced 22 K Ω .
- Max. input level: + 21 dBm.
- Frequency response: 20 Hz – 20 kHz.
- THD+N: 0.002%.
- Output gain: - 10 dB to + 4 dB (adjustable).
- Output impedance: 600 Ω .
- Main supply: AC 90-245 V , 50-60 Hz.
- Dimensions (WxHxD) : 483 x 44 x 146 mm.
- Weight: 4.6 kg.

Related links

- AUDIOROUTE 208 Manual 